

[multi-format video recorder]

LINE XVR 4N H.265



- “Line XVR” - a multi-format video recorder for connecting up to 4 cameras. “Line” software in a kit.
- Working with cameras of formats

Individual setting for each channel.
- The housing can accommodate hard drive with the volume of 12 terabytes.

► SPECIFICATION FOR ANALOG AHD/TVI/CVI/CVBS CAMERAS

The resolution of analog cameras / FPS AHD/TVI/CVI/CVBS	The processed XVR resolution / FPS	2 analog cameras display/archive FPS per channel	3 analog cameras display/archive FPS per channel	4 analog cameras display/archive FPS per channel
960 H / 25 fps	960 H / 25 fps	25 fps	15 fps	15 fps
720 P / 25 fps	720 N / 25 fps	25 fps	15 fps	15 fps
2 Mп / 25 fps	1080 N / 25 fps	25 fps	15 fps	15 fps

Admintool may be used for XVR maintenance:

- Updating firmware.
- Network setup.
- Saving and restoring settings.
- Collecting service logs.

For detailed adjustment of the video server and configuring IP cameras, you can use a Line software workstation or a local management.

Various Line devices may be integrated into a single interface.

Support for the “Line Cloud” service:

- Online monitoring of the video surveillance system.
- SMS and E-mail notifications.
- DynamicDNS domain name service.
- Logging the DVR status.
- FTP archive for storing important videos.
- Connecting to the recorder without a white IP via TURN.

- Support for formats HD-TVI, AHD, CVI, CVBS and IP
- Support for USB mouse
- Support for analytics in the archive
- Support for joint work with other Line software-based servers
- Support for “Line Cloud” service
- Support for “Line.Retransmitter” service
- Support for products of 152 leading manufacturers of IP cameras
- Support two 3.5” hard drive for archive storage*



4 video channels



4 audio channels

* HDD is not included into any scope of delivery of Line video recorders.

Support for ONVIF protocol and RTSP stream

Line 7 SW

Without software restrictions:

- remote monitoring and viewing the archive,
- full-fledged remote administration,
- extended user rights,
- a web server,
- viewing from mobile devices running on iOS, Android.



3 years warranty

Specifications:

operating system	Linux
network interface	100 Mbps
video outputs	1xHDMI, 1xVGA
other connections	2xUSB2.0
analog video inputs	BNC-4
analog audio inputs	RCA-1
analog audio outputs	RCA-1
HDD	1xSATA (up to 12 Tb)
operating temperature range	0...+55 °C
power	12V /2A/ DC
power consumption	up to 24 W
dimensions, mm	258x230x42
net weight	0,8 kg